Underwater Kinetics

13400 Danielson St. Poway, CA 92064 USA USToll Free (800) 852-7483 / +1 (858) 513-9100 Info@uwk.com / www.uwk.com

Litfinger® LitLink®

The LitFinger® and LitLink® are the world's first hotstick lights (patent pending). Both products have a built-in, high intensity LED light for safe and efficient operations in dark or low light areas. They connect to any major hotstick with a splined universal slotted connector.

The LitFinger has a machined aluminum pointed head for fuse barrel removal or breaking off ice or debris. The LitLink is extremely versatile and can be used with pigtail disconnects, broken bulb removers, bulb biter, saw, tie head, conductor cleaner brush, etc...





LITLINK FEATURES

- 94 Lumens / 4 Hr.
- Bright, unbreakable 1-watt LED light.
- · Light weight aluminum body, only 6.8 oz with batteries.
- · Pointed head for breaking off of ice or debris
- · HI-LOW switch for increased battery life
- Water resistant battery compartment with sealed silicone rubber push button
- · Sealed borosilicate window to resist heat and flash
- Passed 3000 V, 8000 A, 1/2 sec (30 cycles) arc blast test
- Easy access (no tools required) battery compartment door
- Universal splined slotted connector attaches to hot sticks
- Runs on three (3) AAA alkaline or lithium (cold weather use) batteries.
- Waterproof to 1 meter



LITFINGER FEATURES

- 94 Lumens / 4 Hr.
- Bright, unbreakable 1-watt LED light.
- Light weight aluminum body, only 7 oz with batteries
- HI-LOW switch for increased battery life
- Notched straight arm to secure fuse while lowering or raising fuse barrel
- · Curved arm for hanging
- Water resistant battery compartment with sealed silicone rubber push button
- · Sealed borosilicate window to resist heat and flash
- Passed 3000 V, 8000 A, (10 cycles) arc blast test at 7 inches from the 12 inch arc
- Easy access (no tools required) battery compartment door
- Universal splined slotted connector attaches to hot sticks
- Runs on three (3) AAA alkaline or lithium (cold weather use) batteries
- Waterproof to 1 meter



PART NUMBERS

516002 UK LITLINK 516001 UK LITFINGER

